





Functional Parameter

Capacity	Max User	10,000
	Max Log	200,000
Inferface	Comm.	TCP/IP, USB Host, Mini USB, RS232 WiFi, Optional 4G
	Relay	1 Relay
Feature	Identification Mode	Card, Password
	Verification Speed	<0.5 Sec
	Self-defined Status	8
	Workcode	Yes
	Software	Anviz Crosschex
	Platform	Linux
Hardware	CPU	Dual 1.0 GHZ High Speed CPU
	LCD	3.2" TFT
	LED	Three-color indicator light
	RFID Card	Standard 125KHz EM ,Optional 13.56MHz Mifare
	Dimensions	204x139x38mm(8.0x5.5x1.5")
	Operating Temperature	-30°C to 60°C
	Humidity Verification	10% to 90%
	Power	DC 12V/Optional battery
	Certificates	CE, FCC, RoHS

Features

- Linux platform provides a safe and stable performance
- Comparison time less than 0.5s
- Ergonomic design with new touch keypad provides a better user experience
- TCP/IP & WiFi & 4G are provided to satisfy different needs
- Provide 1 relay for belling and connecting to Access Control system
- RS232 interface can be connected to a Time & Attendance printer
- New material that makes it more appealing and durable
- Bigger and brighter 3.2 inch color display
- Fast & easy installation through a wall-mounted panel
- Ease the experience of user by brand new UI design

Cloud Management Systerm



Advantages

- No need to install, maintain, or upgrade software
- No expensive computers to purchase or maintain
- Access data in real-time from any PC and Mobile with Internet
- Receive real-time alerts to your email
- Multiple encryptions and redundancy backup for data safety.





Please scan this QR code to get CrossChex Cloud App

For more information, visitwww.anviz.com or email us press@anviz.com