








Baggage Reclaim
Way Out
International Arrivals
Information

Surveillance

Easier and Smarter

ANVIZ[®]
Intelligent . Security






SMB Channel Recommended Camera

Model	Easyview		Ecoview	Hiview			Justview		
Series	EA4502-IRA	EA4502-IREB	EC4502-IREB	HI4501-IRE	HI4501-IREW 	HI2702-IRE	JU4502-IRE	JU4502-IREW 	JU2702-IRE
Product Image									
Resolution	2mp			4mp			2mp		4mp
Image Sensor	1/2.9" Progressive Scan CMOS								
Lens	4mm			2.3mm			4mm		
WDR	Support								
Horizontal Angle of View	77°			105°			77°		
Minimal Illumination	0.01 Lux @(F1.2,AGC ON); 0 Lux with IR								
Frame Rate	30fps (1920×1080, 704×576)					20fps (2560×1440, 704×576)	30fps (1920×1080, 704×576)		20fps (2560×1440, 704×576)
IR Distance	25m			15m			25m		
Day/Night	IR Cut Filter								
Electronic Shutter Time	1S-1/100,000S								
Audio	N/A						Support 1 channel		
Compression	H.264, MJPEG, Anviz Smart Stream								
internet interface	RJ-45(10/100/1000Base-T)								
Supported Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, ONVIF								
Alarm input output	N/A								
Power	DC12V	DC12V/PoE(802.3af)		DC5V/PoE(802.3af)			DC12V/PoE(802.3af)		
Working Temperature	-30°C to 40°C (-C24IP22°F to 104°F)								
Protection	IP53	IP66		IP53					
Edge Storage	N/A		Support up to 128G micro SD card (suggest class 10)						
Smart Function	3DNR, BLC, Motion Detection								
Dimension	Φ92.4*65.1mm	Φ69.2*146mm	154*70*70mm	Φ74*178mm			Φ100*48mm		
Weight	248g	315g	315g	234g			155g		

Project recommended and smart IPC

Series	TopView				OpenView				SuperView	
Model	TO2508-IRE	TO2508-IZRE	TO2708-IRE	TO2708-IZRE	OP2508-IRE	OP2508-IZRE	OP2708-IRE	OP2708-IZRE	SU2508-ZE	SU2708-ZE
Product Image										
Resolution	2M		4M		2M		4M		2M	4M
Image Sensor	1/2.8" CMOS									
Lens	2.8-12mm/F1.4 Φ14 / P-Iris(-Z Model)(Auto and Vari Focus for Z model)									
WDR	More than 120DB true WDR									
Horizontal Angle of View	27°- 92°									
Minimal Illumination	0.001Lux									
Frame Rate	Main Stream (1920×1080@30fps), Sub Stream (704×576@30fps)		Main Stream (2560*1440@25fps) Sub Stream (704×576@30fps)		Main Stream (1920×1080@30fps), Sub Stream (704×576@30fps)		Main Stream (2560*1440@25fps) Sub Stream (704×576@30fps)		Dual Stream Main(1920×1080@30fps), Sub(704×576@30fps)	Dual Stream Main(2560*1440@25fps) Sub(704×576@30fps)
IR Distance	50-70m								N/A	
Day/Night	IR Cut Filter								N/A	
Electronic Shutter Time	1/3s~1/100000s									
Audio	1-ch 3.5 mm audio interface, 1 built-in Microphone 1-ch 3.5mm audio interface									
Compression	H.264, MJPEG, G.711 for audio compression									
internet interface	RJ-45 (10/100/1000Base-T)									
Supported Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS									
Alarm input output	1 in and 1 out (Network disconnect, IP address conflict, Storage exception)									
Power	DC12V/PoE(802.3af)									
Working Temperature	-30°C to 60°C (-22°F to 140°F)									
Protection	IP66/IK10				IP66				IP53	
Edge Storage	Support up to 128G micro SD card (suggest class 10)									
Smart Function	3DNR, BLC, Privacy Mask, Motion Detection, ROI, Smart IR									
Dimension	Φ156*110mm (Φ6.14"*4.33")				Φ96*269mm (Φ3.78"*10.6")				42.5*68.8*128mm (1.67"*2.71"*5.04")	
Weight	1128g (2.49 pounds)				1066g (2.35pounds)				350g (0.77 pounds)	

Smart Storage

Series	EcoStore		MiniStore		TurboStore		EverStore
Model Number	NEA114-1	NCS115-2	NMS114-1	NMS115-1	NTS135-4	NTS137-4	NES127-8
Product Image							
Network Video Input	8 Channel	16 Channel	8 Channel	16 Channel	16 Channel	32 Channel	32 Channel
Record Rate	Up to 100Mbps				Up to 200Mbps		Up to 260Mbps
Audio Input	1 Channel, Support IPC Sync Audio Input						
HDMI Output	1 Channel						
VGA Output	1 Channel						
Audio Output	1ch Sync Video Output						
Compression	H.264/MPEG4/MJPEG						
Recording Resolution	1080P/720P						
Playback	1ch@1080P				4ch@1080P		
Stream Transmission	Support						
Recording Mode	Manual, Motion Detection, Schedule, Alarm						
Backup Mode	HDD, USB HDD, USB CD&DVD-RW						
HDD	1* SATA Port support 2.5" harddisk	2* SATA Port support 3.5" harddisk	1* SATA Port support 3.5" harddisk	1* SATA Port support 3.5" harddisk	4* SATA Port support 3.5" harddisk	4* SATA Port support 3.5" harddisk	8* SATA Port support 3.5" harddisk
Maximum Storage	Up to 4TB	Up to 8TB	Up to 4TB	Up to 4TB	Up to 16TB	Up to 16TB	Up to 32TB
Voice Intercom	1 Channel						
Network Interface	5*RJ45 10/100Mbps (4 POE)		1*RJ45 10/100Mbps				2*RJ45 10/100/1000Mbps
USB	2*USB Ports				3*USB Ports		
Network Function	IPv4, IPv6, HTTP, UPnP, NTP, SNMP, PPPoE, DNS, FTP, ONVIF, GB/T28181						
Power Supply	DC48V 1.5A		DC12V 2A		DC12V 5A		AC100~240V
Power Consumption	≤72W	≤20W			≤50W		≤40W
Working Environment	-10 C ~ +55 C/10%~ 90%						
Dimension(W×D×H)	168mm x 122mm x 64mm (6.6"x4.8"x2.5")	173mm x 122mm x 236mm (6.8" x 4.8" x 9.3")	170mm x 233mm x 44mm(6.7"x9.2"x1.7")		170mm x 230mm x 135mm(6.7"x9.0"x5.3")		1.5U, 440mm x 450.8mm x 60mm
Weight	≤0.38kg	1.5kg			≤3.5kg		≤9.5kg